

305-D4X PoE

Mini PTZ Camera 4X Optical Zoom / H.265 / Outdoor / Built-in Audio

- 2.5 inch
- 1080P HD output,with IR-CUT
- Digital Noise Reduction
- Focal Length 2.8-12mm
- Built-in Microphone
- Water resistance:IP66
- Size: Ø160mm*100mm
- PoE+ (802.3at)
- 1/2.7" Progressive Scan CMOS
- 4x Optical Zoom
- Electronic Shutter 1/60 - 1/10,000
- Rotation Range: Level: 0° ~ 340°
Vertical:-3° ~ 90°
- IR Distance ≤150ft (~50m)
- Support P2P



CAMERA	
Image Sensor	1/2.7" F22 Progressive Scan CMOS
Effective Pixels	1920(H) x 1080(V), 2.0 Megapixels
Electronic Shutter Speed	1/60s~1/10,000s
Minimum Illumination	Color: 0.05Lux @F1.6; 0 Lux with IR B/W: 0.005 Lux @ F1.6; 0 Lux with IR
IR Distance	Up to 50m (150ft)
LENS	
Focal Length	2.8mm~12mm
Max.Aperture	F1.6 ~ F2.7
Angle of View	H: 28° ~ 115°
Optical Zoom	4X
Focus Control	AUTO
Minimum Focus Distance	100mm ~ 1000mm
PTZ	
Pan/Tilt Range	Pan: 0° ~ 340° endless; Tilt: -3° ~ 90°
Manual Control Speed	Pan: 0.01° ~80° /s; Tilt: 0.01° ~80° /s
Power up Memory	Restore to the previous PTZ and lens position after power failure

VIDEO & AUDIO	
Video Out	H.264/H.265
Frame Rate	25/30fps@1080P
Day/Night	Support IR-CUT Auto / Color / B/W
OSD Menu	N/A
White Balance	Auto
Focus Control	Support
Noise Reduction	Support
Audio In/Out	I/O
STANDARD	
Power Supply	DC 12V/2A
Power Consumption	25W (IR on)
Operating Conditions	-20 C ~60 C / 10%-90% RH
Ingress Protection	IP66
ONVIF	Support
Certifications	CE: EN55032/EN55024/EN61000-3-2/3 FCC: Part15 subpartB,ANSI C63.4- 2014 ROHS: EC Council Directive 2011/65/EU PSE: J55022(H22) IEC-60825-1
SIZE	
Casing	Polymer
Dimensions	160(mm) x 100(mm)
Net Weight	1.4kg (3lbs)

MOUNTING OPTION

CM-305-A



CM-305-B

